

# Technical Specification Sheet

## PPcP Injection Molding Grade

Recycled Polypropylene Co-Polymer (rPPcP) from post-consumer scrap for injection molding applications.



**Color**  
White

**Source**  
Post Consumer

**Mesh Size**  
2x120

### Applications

- Paint Pails
- Washing Machine
- Pallets

### Packaging & Shipping

- Packaged in 650 KG jumbo bags
- Delivered in 40-foot full container loads (FCL)

### Contact

- Plot 1, South Amghara, Kuwait
- +965 22909901
- [info@beatouna.com](mailto:info@beatouna.com)

	Typical Range	Test Method
Density	0.955 – 0.958 g/cm <sup>3</sup>	ASTM D792
Ash Content	< 2%	Furnace
Moisture Content	< 0.3%	Gravimetric
Melt Flow Index (MFI)	15 - 19 g/10 min	ASTM D1238 (190°C/5kg)

All data regarding the chemical and physical properties of materials shared by BRC are based on controlled testing and are provided for guidance only. These figures are indicative and subject to variation based on processing conditions and production site specifics. It remains the responsibility of the customer to conduct their own assessments to ensure the material's suitability for their specific application. BRC accepts no liability for the use or handling of materials or reliance on the provided information.



**BEATOUNA**